

CEDIA  
BEST NEW  
PRODUCT  
WINNER

ESX  
INNOVATION  
AWARDS  
WINNER

2020 CE PRO  
BRAND LEADERS

2020 CE PRO  
BULLET BRAND

CEPro  
Brand Leader  
Water Leak Detection  
2021

# Single Point Leak Detection & Automatic Shut-Off

## Help stop extensive water damage before it can begin with WaterCop® Leak Stop+ systems.

Leak Stop+ detects plumbing leaks at a single location, sounds an audible alarm, and automatically shuts off the water supply. The addition of an RJ45 Jack makes Leak Stop+ capable of integrating with SmartConnect to receive notifications. It is also capable of integrating with home security or automation systems to provide notifications when the shut-off system has been activated. They are ideal solutions for water heaters, recirculation pumps and softeners which become particularly vulnerable to leaks as they age.



Valve can be controlled independently of water leaks by pushing the **open/close soft touch buttons** on the front of the actuator

**Shut-off valve** remains closed until it is manually reset

**Audible alarm** sounds when a leak is detected

Features a new **RJ45 Jack** for integration with SmartConnect or security/home automation systems

**Constantly monitors** selected area for accumulating moisture

Features **brass ball valve** and **electric actuator** with two attached moisture sensors  
**Now available with 1 or 2 rope sensors**

**Leak Stop+** provides signal output to third party devices to notify of shut-off

The proven leader in household leak protection: **is there when you're not.**

# Leak Stop+: Protection for your appliances – and your property.

## WaterCop® Leak Stop+ Systems

Designed for plumbing supply line installation upstream of the appliance or area you wish to monitor – most commonly a water heater. Place the two sensor probes in the area where water would first accumulate if a leak occurs.

The Leak Stop+ unit can be integrated with SmartConnect or security/home automation systems to provide notifications when the shut-off system has been activated. Please note Leak Stop+ does not operate with other WaterCop® wireless sensors.

## Leak Stop+ Specifications

- **Max working pressure:** 125 PSIG
- **Ambient temperature:** 35° to 105° F
- **Voltage – Leak Stop:** 12 VDC 1 phase (includes 115 V wall transformer and 20' cord)
- **Valve:** NSF/ANSI 372\* approved lead-free, full port brass
- **Installation Consideration:** Building and plumbing codes in some areas may require installation by a licensed plumber

\* Lead Free NSF/ANSI 372 refers to the wetted surface of pipe, fitting and fixtures in potable water systems that have a weighted average lead content ≤ 0.25%. Source: California Health & Safety Code (116875); Vermont Act 193.

## Ordering Information

SIZE (FNPT)	PART NO. W/ 2 PROBES	PART NO. W/ 1 ROPE	PART NO. W/ 2 ROBES
½"	WCLSLFB ½	WCLSLFBR ½	WCLSLFB2R ½
¾"	WCLSLFB ¾	WCLSLFBR ¾	WCLSLFB2R ¾
1"	WCLSLFB 1	WCLSLFBR 1	WCLSLFB2R 1
1¼"	WCLSLFB 1¼	WCLSLFBR 1¼	WCLSLFB2R 1¼

Note: All sizes are lead-free NSF/ANSI 372

## SmartConnect WiFi & Mobile App

Receive mobile alerts and control your WaterCop system with the SmartConnect (WCSCLV) mobile app interface.



Probe version pictured



To order or for additional information, visit

or call 800-545-3636.