



**NOTE: WCDACTHW HAS 1 SENSOR CABLE ATTACHED
WCDACTHW2 HAS 2 SENSOR CABLES ATTACHED**

**ALL VALVES ARE CERTIFIED TO
NSF/ANSI 372 FOR USE WITH POTABLE WATER**

Enclosure: Polycarbonate
Power: Power Converter With 20' Cord
Controls: Local Controls
Valve: Full Port Brass Ball Valve
Frequency: 418 MHz

Model	Valve Size	A	B	C	D	E	F	G	H	Flow GPM
WCDACTHW	-	-	-	-	.74	3.78	4.10	5.00	4.05	-
WCDACTHW	1/2	1/2 - 14 NPT	2.60	4.78	.74	3.78	4.10	5.00	4.05	19
WCDACTHW	3/4	3/4 - 14 NPT	2.90	5.02	.74	3.78	4.10	5.00	4.05	34
WCDACTHW	1	1 - 11-1/2 NPT	3.56	5.19	.74	3.78	4.10	5.00	4.05	52
WCDACTHW	1-1/4	1-1/4 - 11-1/2 NPT	3.66	5.18	.74	3.78	4.10	5.00	4.05	77

**UNCONTROLLED
DRAWING**

THIS PRINT IS THE PROPERTY OF DYNAQUIP CONTROLS AND SHALL NOT BE COPIED, REPRODUCED, LOANED, OR DISPOSED OF DIRECTLY OR INDIRECTLY, NOR USED FOR ANY PURPOSE OTHER THAN THAT FOR WHICH IT IS SPECIFICALLY FURNISHED EXCEPT BY WRITTEN PERMISSION OF DYNAQUIP CONTROLS.

NO. **WaterCop Classic HW** FILE NO. SUB389

TITLE **Actuator with Hard Wired Sensor shown with valve attached**

DR MJP DATE 07-25-18 CHKD MJP DATE 03-07-17 ENGR MJP DATE 032-07-17

