

Builder Valve

An inexpensive, essential component that provides property owners with the option to put in a leak detection system during construction or at a later date.

Easy to spec. Easy to install. Essential for every new home.

Integrators and builders can save considerable time and contractor cost by specifying installation of the WaterCop® ready Builder Valve at rough in. This unique WaterCop® ready brass valve* comes complete with a fully functional handle for long-term manual operation. This handle can be removed to automate the valve at any future date.

While most homeowners will choose to install the remaining WaterCop® components prior to move in, some may wait for a future date. A tag is placed on every builder valve identifying it as part of a WaterCop® system. Builders and integrators will be able to attach company information to this tag so the homeowner has a clear purchase path when they decide to finish installation of a WaterCop® system.


Having this low cost valve installed as standard on every home will reduce sub cost and time while increasing your sales opportunities.

ITEM	DESCRIPTION
WCMVLF ½	½" LEAD FREE BRASS WATERCOP BUILDER VALVE W/HANDLE
WCMVLF ¾	¾" LEAD FREE BRASS WATERCOP BUILDER VALVE W/HANDLE
WCMVLF 1	1" LEAD FREE BRASS WATERCOP BUILDER VALVE W/HANDLE
WCMVLF 1¼	1¼" LEAD FREE BRASS WATERCOP BUILDER VALVE W/HANDLE

Note to builder: A standard 120VAC GFCI (consult local electrical codes) outlet should be located within 6 feet of the WaterCop® valve.

*Lead Free ANSI/NSF 372 refers to the wetted surface of pipe, fittings and fixtures in potable water systems that have a weighted average lead content ≤ 0.25% Source: California Health & Safety Code (116875); Vermont Act 193.

The installation process is very simple:



Install WaterCop® Builder Valve during plumbing rough-in.



Remove manual valve handle using a flat head screwdriver.



Fit WaterCop® actuator to the valve and install remainder of system.

To order or for additional information, visit watercop.com or call 800-545-3636.

