



ENCLOSURE: POLYCARBONATE
 POWER: POWER CONVERTOR WITH 20' CORD
 DISPLAY: BACK LIGHTED LCD
 CONTROLS: LOCAL CONTROLS WITH MANUAL OVERRIDE
 VALVE: FULL PORT BRASS BALL VALVE

ALL VALVES ARE CERTIFIED TO NSF/ANSI 372 FOR USE WITH POTABLE WATER

MODEL	VALVE SIZE	A	B	C	D	E	F	G	FLOW GPM
WPACT	1/2	1/2 - 14 NPT	2.60	4.78	.74	3.78	4.10	5.00	19
WPACT	3/4	3/4 - 14 NPT	2.90	5.02	.74	3.78	4.10	5.00	34
WPACT	1	1 - 11-1/2	3.56	5.19	.74	3.78	4.10	5.00	52
WPACT	1-1/4	1-1/4 - 11-1/2 NPT	3.66	5.18	.74	3.78	4.10	5.00	77

UNCONTROLLED DRAWING

THIS PRINT IS THE PROPERTY OF DYNAQUIP CONTROLS AND SHALL NOT BE COPIED, REPRODUCED, LOANED, OR DISPOSED OF DIRECTLY OR INDIRECTLY, NOR USED FOR ANY PURPOSE OTHER THAN THAT FOR WHICH IT IS SPECIFICALLY FURNISHED EXCEPT BY WRITTEN PERMISSION OF DYNAQUIP CONTROLS.

NO. **WATERCOP PRO** FILE NO. SUB221

TITLE **VALVE ACTUATOR**

DR MJP DATE 07-25-18 CH'KD MWS DATE 08-21-15 ENGR MWS DATE 08-21-15

