



ALL VALVES ARE CERTIFIED TO NSF/ANSI 372 FOR USE WITH POTABLE WATER

Model	Valve Size	Α	В	С	D	E	F	G	Н	Flow GPM
WCDACT	-	-	ı	-	.74	3.78	3.25	5.00	4.05	-
WCD 1/2	1/2	1/2 - 14 NPT	2.60	4.78	.74	3.78	3.25	5.00	4.05	19
WCD 3/4	3/4	3/4 - 14 NPT	2.90	5.02	.74	3.78	3.25	5.00	4.05	34
WCD 1	1	1 - 11-1/2 NPT	3.56	5.19	.74	3.78	3.25	5.00	4.05	52
WCD 1 1/4	1-1/4	1-1/4 - 11- 1/2 NPT	3.66	5.18	.74	3.78	3.25	5.00	4.05	77

Enclosure: Polycarbonate Power: Power Converter With 20' Cord Controls: Local Controls Valve: Full Port Brass Ball Valve Frequency: 418 MHz

UNCONTROLLED DRAWING

THIS PRINT IS THE PROPERTY OF DYNAQUIP CONTROLS AND SHALL NOT BE COPIED, REPRODUCED,LOANED, OR DISPOSED OF DIRECTLY OR INDIRECTLY, NOR USED FOR ANY PURPOSE OTHER THAN THAT FOR WHICH IT IS SPECIFICALLY FURNISHED EXCEPT BY WRITTEN PERMISSION OF DYNAQUIP CONTROLS.

NO. WaterCop Classic

Actuator shown with valve attached

MJP 07-02-25 MJP 032-07-17 MJP DATE 03-07-17



FILE NO.
SUB352