



WPKHXXD OPTIONAL

## **ALL VALVES ARE CERTIFIED TO NSF/ANSI 372 FOR USE WITH POTABLE WATER**

Model	Cable Length	Hardwired Sensors	
WPK25D	25'	No	
WPKH25D	25'	Yes	
WPK50D	50'	No	
WPKH50D	50'	Yes	
WPK75D	75'	No	
WPKH75D	75'	Yes	
WPK150D	150'	No	
WPKH150D	150'	Yes	

	Valve Size	А	В	С	Flow GPM	UNCONTROLLED DRAWING THIS PRINT IS THE PROPERTY OF DYNAQUIP CONTROLS AND
_	1/2	1/2 - 14 NPT	2.60	4.78	19	SHALL NOT BE COPIED, REPRODUCED,LOANED,
	3/4	3/4 - 14 NPT	2.90	5.02	34	OR DISPOSED OF DIRECTLY OR INDIRECTLY, NOR USED
	1	1 - 11-1/2 NPT	3.56	5.19	52	FOR ANY PURPOSE OTHER THAN THAT FOR WHICH IT IS SPECIFICALLY FURNISHED EXCEPT BY WRITTEN
	1 1/4	1-1/4 - 11-1/2 NPT	3.66	5.18	77	PERMISSION OF DYNAQUIP CONTROLS.

## **POWER SUPPLY INCLUDED**

DRAWING
THIS PRINT IS THE PROPERTY
OF DYNAQUIP CONTROLS AND
SHALL NOT BE COPIED,
REPRODUCED,LOANED,
OR DISPOSED OF DIRECTLY
OR INDIRECTLY, NOR USED
FOR ANY PURPOSE OTHER THAN
THAT FOR WHICH IT IS
SPECIFICALLY FURNISHED
EXCEPT BY WRITTEN
PERMISSION OF
DYNAQUIP CONTROLS.

NO.	Wat	terC	op Pi	ro		FILE NO.	345
WaterCop Pro Integrated Indoor Dual							
DR	07-03-25	CH'KD	DATE	1 [	ENGR I	DATE	1 [
MDC	07-03-25	INIAA2	00-23	-15	ININA	00-23	-15
			<b>.</b>	&			

