









Dual Valve Automatic Water Shut-Off System

A more efficient way to control water shut-offs in properties with two incoming water lines.

Perfect for condominiums, apartments, villas, attached homes, and commercial breakroom pantries using multiple line water feeds. Shut-off valves open/close simultaneously when notified by sensors, alarm panel or compatible SmartConnect WiFi device and app.

WaterCop® Classic Dual Valve System

An unlimited amount of wireless sensors communicate with shut-off valves installed indoors. Simple to install and use, this system provides an enhanced level of leak protection with a SmartConnect device and mobile app.













Provides leak protection for homes with two incoming water lines.

WaterCop® Classic Dual Valve System



Features

- NSF/ANSI 372* approved lead-free brass, full flow, 600 psi rated industrial valve
- Sizes $\frac{1}{2}$ " $\frac{1}{4}$ " standard ($\frac{1}{2}$ " to 2" large valve integration available)
- Onboard open/close buttons and indicator lights on indoor control unit
- Internal antenna on actuator and wireless sensors
- · Single or dual wireless sensors available
- 10' white sensor cord with corrosion-resistant gold-plated prongs
- Unlimited sensors
- Wireless sensor signal can be enhanced for longer distances (Part No. WCDR)
- · Local open/close water control
- · Connection cable is not direct burial rated
- * Lead Free NSF/ANSI 372 refers to the wetted surface of pipe, fitting and fixtures in potable water systems that have a weighted average lead content ≤ 0.25%. Source: California Health & Safety Code (116875); Vermont Act 193.

Ordering Information

Step One: Select shut-off valve #1 by size

Step Two: Select shut-off valve #2 by size

SIZE (FNPT)	PART NO. (LEAD FREE NSF/ANSI 372*)
1/2"	WCVLF 1/2
3/4"	WCVLF ¾
1"	WCVLF1
11⁄4"	WCVLF11/4

Step Three: Add WaterCop® Classic Dual Kit

- WCDACTDUAL (5' plenum cable between valves) or
- WCDACTDUALHW for 1 Hard-wired Sensor or
- WCDACTDUALHW2 for 2 Hard-wired Sensors

Step Four: Add WaterCop® Classic components

PART NO.	DESCRIPTION
WCDFS1	SINGLE WIRELESS SENSOR
WCDFS2	DUAL WIRELESS SENSOR
WCDR	SENSOR RANGE ENHANCING REPEATER
WPA	SENSOR AC POWER ADAPTER
RS100	WATER CONTROL WALL SWITCH
CBL50	VALVE/SWITCH INTERCONNECT CABLE (50')
CBL100	VALVE/SWITCH INTERCONNECT CABLE (100')
WCSC2	SMARTCONNECT WIFI MOBILE APP INTERFACE

SmartConnect

Receive mobile alerts and control your WaterCop system using the WaterCop app on a phone or tablet. SmartConnect is compatible with Classic, Pro and LeakStop+ systems.

- 24/7 remote mobile control and access to your WaterCop system
- WiFi compatible







