



**ALL VALVES ARE CERTIFIED TO NSF/ANSI 372 FOR USE WITH POTABLE WATER**

Enclosure: Polycarbonate  
 Power: Power Converter With 20' Cord  
 Controls: Local Controls  
 Valve: Full Port Brass Ball Valve  
 Frequency: 418 MHz

Model	Valve Size	A	B	C	D	E	F	G	H	Flow GPM
WCDACTDUAL	-	-	-	-	.74	3.78	4.10	5.00	4.05	-
WCDACTDUAL	1/2	1/2 - 14 NPT	2.60	4.78	.74	3.78	4.10	5.00	4.05	19
WCDACTDUAL	3/4	3/4 - 14 NPT	2.90	5.02	.74	3.78	4.10	5.00	4.05	34
WCDACTDUAL	1	1 - 11-1/2 NPT	3.56	5.19	.74	3.78	4.10	5.00	4.05	52
WCDACTDUAL	1-1/4	1-1/4 - 11-1/2 NPT	3.66	5.18	.74	3.78	4.10	5.00	4.05	77

**UNCONTROLLED DRAWING**

THIS PRINT IS THE PROPERTY OF DYNAQUIP CONTROLS AND SHALL NOT BE COPIED, REPRODUCED, LOANED, OR DISPOSED OF DIRECTLY OR INDIRECTLY, NOR USED FOR ANY PURPOSE OTHER THAN THAT FOR WHICH IT IS SPECIFICALLY FURNISHED EXCEPT BY WRITTEN PERMISSION OF DYNAQUIP CONTROLS.

NO. **WCDACTDUAL** FILE NO. SUB391

TITLE **Actuator shown with valve attached**

DR MJP DATE 07-02-25 CHKD MJP DATE 03-07-17 ENGR MJP DATE 032-07-17

